



SC-5000

2D DESKTOP BARCODE SCANNER

PERFORMANCE		
IMAGE SENSOR		640 * 480 CMOS
LIGHT SOURCE		4PCS WHITE LED
SYMBOLLOGIES	2D	PDF417, Data Matrix, QRCode, Micro QR
	1D	Code 128, UCC/EAN-128, AIM 128, EAN-8, EAN-13, ISSN, ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-14, Matrix 2 of 5(European Matrix 2 of 5), Industrial 2 of 5, Standard 2 of 5, Code 39, Codabar, Code 93, Code 11, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand etc.
RESOLUTION		1D≥5mil 2D≥10mil
DEPTH OF FIELD	EAN13	20mm-200mm (13mil)
	Code 39	10mm-100mm (5mil)
	QR Code	5mm-180mm (15mil)
	PAYMENT CODE (PHOE)	20mm-450mm
PCS		10%
INTERFACE		USB-HID , USB-VCOM, UART (DUE TO ORDER)
MECHANICAL / ELECTRICAL		
SIZE		110*150*122(mm)
WORKING MODE		TRIGGER MODE, AUTO-SENSOR, CONTINUOUS SCAN
WEIGHT		348g(WITH CABLE)
INOUT VOLTAGE		5VDC±10%
CURRENT		Operating : 210mA±10mA ; Standby : 130±5mA ;
ENVIRONMENTAL		
OPERATING TEMPERATURE		0°C to 45°C
STORAGE TEMPERATURE		-20°C to 60°C
HUMIDITY		5%~90% (no-condensing)
SHOCK RESISTANCE		1.0M FREE FALL TEST
CERTIFICATE		
CERTIFICATE		FCC Part15 Class B, CE EMC Class B
VERSIONS OF SPECIFICATION		
VERSIONS		V1.1