

DC-200

2D Barcode Scanner



PERFORMANCE

IMAGE SENSOR		640*480 pixels
LIGHT SOURCE		360nm-830nm WHITE LED
AIMING LIGHT SOURCE		635nm RED LED
	2D	QR Code、PDF417、DataMatrix、Chinese Sensible Code、 HANXIN Code
SYMBOLOGIES	1D	Code 128、EAN-8、EAN-13、UPC-E、UPC-A、Code 39、Code 32、Trioptic 39、Codabar、Code 93、ITF 25、Matrix 25、Industrial 25、Airline 25、Plessey、MSI、Code 11、GS1-Databar、Compsite、Aztec Code、AU Postal Code、Codablock A&F、ENG Postal Code、JP Postal Code、KIX Postal Code、Pharma Code、PLANET Code、POSTNET Code、Royal Infomail Code、Telepen、Trioptic Code、UPU Postal Code、
RESOLUTION		≥4mil
DEPTH OF FIELD	EAN13 (13mil)	35mm-270mm
	QR Code (10mil)	20mm-100mm
PRINT CONTRAST RATIO		≥ 20%
DECODING RATE		30 scans/sec
AUTO-INDUCTION		Optional
STAND		Optional

MECHANICAL / ELECTRICAL

INTERFACE		USB HID-KBW ,RS232 (Optional),VCOM (Optional)
WORKING VOLTAGE		5V
CURRENT @ 5 VDC	Operating	240mA
	Standby	100mA
DEMENSIONS		173(L)×68 (W)×76 (H)mm
WEIGHT		145g(No Stand and line)

ENVIRONMENTAL

OPERATING TEMPERATURE	-10°C - 60°C
STORAGE TEMPERATURE	-20°C - 70°C
HUMIDITY	5%~95% (non-condensing)

DATASHEET

DATASHEET	V1.0
-----------	------