

SC-1000

1D Wireless Barcode Scanner



PERFORMANCE

LIGHT SOURCE		1D Laser, Red LED 650nm ± 10%
SYMBOLOGIES	1D	Code128、EAN-13、EAN-8、Code39、UPC-A、UPC-E、Codabar、Interleaved 2 of 5、ISBN/ISSN、Code93、Code11、UCC/EAN-128、GS1 Databar...
RESOLUTION		≥ 4mil for 1D
DEPTH OF FIELD	EAN13 (13mil)	0 ~ 75mm (13mil EAN13 PCS 90%)
PRINT CONTRAST RATIO		≥ 30%
READING WIDE		5mm ~ 300mm
FIELD OF VIEW		Horizontal: 70° , Vertical : 70°

WIRELESS TRANSMIT

REQUENCY	2.4G wireless transmission
COMMUNICATION RANGE	20 ~ 30 meters in open area
PAIRING ABILITY	Base station support up to 4 scanners connection
MEMORY	Save over 2,000 scans data (@ barcode length < 15 bytes)

MECHANICAL / ELECTRICAL

INTERFACE	USB HID
WORKING VOLTAGE	5 VDC ± 10%
CURRENT @ 5 VDC	Operating : 130mA, Standby : 20mA, Peak : 220mA
POWER SOURCE	USB from base station
BATTERY	3.7V 1000mAh Li-ion
WORKING TIME	Working : 20hours, Standby : 3 months
DEMEASUREMENTS	Scanner with cradle : 227(L) × 107 (W) × 138 (H)mm
WEIGHT	415g

ENVIRONMENTAL

OPERATING TEMPERATURE	-20°C ~ 60°C
STORAGE TEMPERATURE	-40°C ~ 90°C
HUMIDITY	5% ~ 95% (no-condensing)
AMBIENT LIGHT	0 ~ 100,000lux (nature light)
ESD	±9 KV (contact discharge), ±15 KV (air discharge)

SAFETY

EN55022: 2006+A1:2007 EN55024:1998+A1:2001+A2:2003
±9 KV (contact discharge); ±15 KV (air discharge)