

TX-1010M

All in One Multi-Touch POS

- Multi Touch Capacitive Touch Screen; 10 Fingers
- Different SSD and HDD Driver Capacity Options
- High Quality Case, Aluminum Casting & Plastic
- Selectable Different CPU Classes (BayTrail J1800 / J1900, Core- i3 / i5 / i7)
- Fanless Cooling (No Ventilation)
- Multiple Connect Options 4 x USB 2.0, 2 x USB 3.0, 1 x Ethernet, 2 x RS232
- Supporting MSR & RFID are Optional
- Vesa Mounting Slots
- CE Certificate Conformity
- 2 Years Warranty



MODEL	J1800 / J1900	i3 / i5 / i7
Processor	Intel® BayTrail J1800 / J1900 CPU	Intel® Core™ i3 / i5 / i7 CPU
Chipset	Intel® Bay Trail SOC Chipset	Intel® Hm65 / Hm76 / Hm77 / Hm86,ETC (Option)
Memory (RAM)	2GB / 4GB / 8GB DDR3 1600Mhz	4GB / 8GB / 16GB / 32GB DDR3/DDR4 1333Mhz to 2666Mhz
Graphics Memory	Intel® HD Graphics	Intel® HD / UHD Graphics
Flash Disk	120 GB SSD HDD 2.5" /MSATA	120 GB SSD HDD 2.5" / MSATA / M2
HDD	1 x HDD 2.5"	1 x HDD 2.5"
Touch Panel	10.1" LED LCD Panel Capacitive Touch	10.1" LED LCD Panel Capacitive Touch
Resolution	1366 x 768	1366 x 768

INPUTS / OUTPUTS		
VGA	1	1
Power Button	1	1
USB	2 x USB 2.0 + 2 x USB 3.0 (Option)	2 x USB 2.0 + 2 x USB 3.0 (Option)
Serial/COM	2 x RS-232 1 x LPT (Option)	2 x RS-232 1 x LPT (Option)
LAN	1 & 2 LAN 10/100/1000 (Option)	1 & 2 LAN 10/100/1000 (Option)
Cash Drawer	1 x RJ 11 (12V / 24V) (Option)	1 x RJ 11 (12V / 24V) (Option)
Display Port	1 (for 2nd screen)	1 (for 2nd screen)
HDMI	1	1

DRIVERS	
Customer Display	Graphic Customer Display (High Readability) (Option)
Dimensions(W x H x D)	265 x 200 x 190mm / (working position tilted at 45°)
Power Supply	Adapter 12V / 4-10A
Net Weight	3.2 kg / (not including power supply or customer display)
Materials	High Quality Case, Aluminum Casting & Plastic
Colors	Black
Comptabile OS	Windows 7, Windows 8.1, Windows 10, Posready 7

OPTIONS & PERIPHERALS	
Graphic customer display (high readability)	
Cards, Dallas keys - & Addimat readers	
2 nd screen (dual screen system)	